


MINI ATTACHMENTS

TRENCHER




- 24", 30", 36" & 48" digging depths
- 6" to 12" wide chains available
- Operating pressure (psi) 2,000 to 3,000
- GPM requirements 6-10 or 10-16
- Standard tooth, shark tooth, or combo available
- Offset footing model available (615F)

Specifications	615			615F	
	24"	30"	36"	24"	30"
Trench Depth w/Auger @ 65° Angle	24"	30"	36"	24"	30"
Chain widths	6", 8", 10", 12"	6", 8", 10'	4.5", 6", 8"	6", 8", 10", 12"	6", 8", 10'
Recommended Trenching Angle	65°	65°	65°	65°	65°
Length (overall)	51"	58"	65"	65"	72"
Width (overall)	42"	42"	42"	26"	26"
Height (overall)	28"	28"	28"	29"	29"
Spoil Discharge Reach	24"	24"	24"	18"	18"

BRADCO

VIBRATORY ROLLER




- 36" smooth drum
- Use on sand, gravel, soils, crushed stone and other aggregates
- Steel drum has an adjustable steel scraper blade

Specifications	
Smooth Drum	36"
Width (overall)	42"
Drum Width	36"
Height (overall)	22"
Length (overall)	34"
Drum Diameter	20"
Operating Weight (lbs)	840
Dynamic Force (lbs)	2,488
Vibrating Speed (vpm)	2,000
Vibrating Weight (lbs)	507
Drum Oscillation/Tilt	15°
Hydraulic Motor Flow (GPM)	6 to 9 or 10 to 14

BRADCO

VIBRATORY PLOW



- 12' turning radius
- Rotating coulters wheel frame mounted
- Optional hydraulic steering assembly
- Optional cable chute blades, reel mount, and pulling accessories available

Specifications	
Width (overall)	24.5"
Height (overall)	27"
Length (overall)	36"
Flow Requirements (GPM)	8 to 14
Operating Pressure (PSI)	1,500 to 3,000
Weight (lbs)	510

BRADCO