







SNOW REMOVAL

For skid-steer loaders, utility loaders, wheel loaders, & backhoe loaders.

FFC provides a variety of snow removal attachments that will get the job done right. So whether you push, pull, or blow snow, FFC has the tools you need.

The FFC Snow Push quickly removes even the heaviest snow without leaving windrows, and with the optional Pull Back Kit, the Snow push gets next to fences and buildings to pull snow away cleanly.

The FCC Snow Blower throws snow as far as 45 feet, features a poly-lined chute and deflector for faster adjustments, and never requires a case drain.

The FFC Snow Bucket provides yet another exceptional tool for your snow removal needs.

With 16 Snow Blade models to choose from, there's an FFC snow Blade that's ideal for your machine and the job. The "New" Trip Edge Blade is also available with a floating tilt which allows for cleaner snow removal across uneven roads.

- 1 year warranty on structure
- 6 month warranty on hydraulics



ONSTRUCTION GROUP

🖬 BRADCO 🔍 🕼 CUSTONWORKS 💉 輝 🕉 HARLEY 🎲 J;B 🖄 MCMILLEN 🕤 SWEEPSTER



Specifications 115 Series							
Model #	Width OD	A Height OD	Angled Cut Width	Weight (Approx)			
11584	84"	32"	69"	1,135 lbs			
11596	96"	32"	79"	1,172 lbs			
11508	108"	32"	88"	1,240 lbs			
11520	120"	32"	98"	1,308 lbs			
11532	132"	32"	108"	1,376 lbs			
11544	144"	32"	118"	1,446 lbs			

Carrier Specifications:

operating weight <20,000 lbs

Models 114, 5700, and 115 are all installed with: • Replaceable wear edge

SNOW BLADE

115 Series angles 35° in either direction hydraulically. Equipped with a ten gauge steel blade. Optional flap which reduces snow spillage. For Large SSL, Compact Utility Loaders, Small Wheel Loaders and Backhoe Loaders.


Continued

- Replaceable wear edge (Optional rubber edge)
- Adjustable skid shoes
- Spring-loaded trip mechanism

126 Series has a cutting edge trip system that allows operator to glide over manholes and curb obstructions without losing gathered material. Angles 30° in either direction hydraulically and has adjustable skid shoes. Equipped with reversible high carbon steel bolt-on edge. 6° floating tilt allows for cleaner snow removal across uneven roads. For Skid-Steers.

Specifications	s 12	6 Series			
Model #	Width OD	A Height OD	Angled Cut Width	Weight (Approx)	
12672	72"	32"	62"	1,056 lbs	
12690	90"	32"	78"	1,122 lbs	
12602	102"	32"	88"	1,165 lbs	Carrier Specifications
12619	119"	32"	103"	1,226 lbs	lift capacities <9,500 lb operating weight <11,0

IMPORTANT: All replacement hydraulic hoses and fittings must have a minimum rated working pressure of 4000 psi. Hoses and hydraulic couplers from the attachment to the loader are included for skid-steer only.



Subject to change without notice.



1	٠,	PALA
-		