

Snow Blowers

FFC Snow Blowers, by Paladin feature a two-stage hydraulic blower that throws snow up to 45 ft. Blower is electrically controlled, and has hydraulically operated poly-lined chute and deflector. Equipped with reinforced wrapper and adjustable skid shoes. Case drains are not required for high-flow models. Has replaceable wear resistant steel tapered wear edge and high-volume 25" or 36" shroud opening. For Skid Steer Loaders and Compact Tool Carriers.

There is an optional Truck Chute Kit for snow blower models 11072G, 11072H, 11078G, 11078H, 11084G, 11084H, 11096G, and 11096H.

When ordering, verify hydraulic flow and pressure of skid-steer. Failure to supply proper flow and pressure could result in motor failure or poor performance.



Specifications											
Model #	Weight (Approx)	Cutting Width	Cutting Height	Depth	Height	Auger Motors	Auger Dia.	Fan Dia.	PSI Range	GPM Range	Hose ID
Standard-Flow Models											
11048A	745 lbs	48"	25"	38"	57"	Single	14"	18"	2000-3000	8-14	.50"
11060C	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	12-17	.50"
11060D	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11060E	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11072D	845 lbs	72"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11072E	845 lbs	72"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11078D	878 lbs	78"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11078E	878 lbs	78"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11084D	895 lbs	84"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11084E	895 lbs	84"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
High-Flow Models											
11072F	1150 lbs	72"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
11072G	1160 lbs	72"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11072H	1160 lbs	72"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11078F	1200 lbs	78"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
11078G	1200 lbs	78"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11078H	1200 lbs	78"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11084F	1190 lbs	84"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
11084G	1240 lbs	84"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11084H	1240 lbs	84"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11096G	1320 lbs	96"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11096H	1320 lbs	96"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"

Carrier Specifications: lift capacities <9,500 lbs operating weight <11,000 lbs

Subject to change without notice.