

DARE TO COMPARE!



THE DRIVE YOU NEED TO GET THE JOB DONE!



DRILLING DRIVES

ANCHOR DRIVES

From 2,000 ft/lb to 300,000 ft/lb, Pengo has a complete line of hydraulic drives for drilling and anchor installation.

From mini-skid steer to 150T Excavator, we offer configurations that range from one, two or variable speed drives dependent on drive size and application.

Note that both theoretical and actual torque values are listed, but that PENGO recommends to go by ACTUAL torque listings.

DRILLING DRIVE "D" SERIES

Designed for Drilling Applications

Part No.	Model	Connection	Speed Config.	Max Flow (gpm)	Max Pressure (psi)	Torque Low (ft/lbs)	Torque High (ft/lbs)	Speed (rpm)	Recommended Prime Mover						Excavator Size (metric tons)	
									Power Pack	Compt Digger Derrick	Compt Excavator	Skid Steer Loader	Digger Derrick	Backhoe (TLB)		Excavator
610650	DS-2	H-200	Sngl	25	3000	0	2356	65		■	■	■				2T - 3T
610652	DS-2	R-256	Sngl	25	3000	0	2356	65		■	■	■				2T - 3T
610172	DS-3	H-200	Sngl	25	3000	0	3859	40		■	■	■				2T - 4T
610173	DT-5	H-250	Two	40	3000	2465	4930	50 / 100		■	■	■		■		3T - 6T
610174	DT-15	H-300	Two	50	3000	7738	15478	20 / 40					■	■	■	12T - 20T
610442	DV-20	H-300	Var	60	4000	13337	22507	24 / 40						■	■	12T - 20T
610384	DV-30	S-400	Var	60	4000	13048	31661	18 / 41							■	15T - 25T
610385	DV-40	130mm	Var	60	4000	15683	38056	14 / 34							■	15T - 25T

- REVOLUTION DRIVES**

 - ✓ Drilling & Anchor Drives
 - ✓ High-Efficient Gear Box
 - ✓ Tru Link™ Compatible
 - ✓ Torque listed at both actual and theoretical
 - ✓ Complete Drive Package

ANCHOR DRIVE "R" SERIES

Designed for Anchor Installation Applications

610659	RS-6X	H-200	Sngl	25	2500	0	6750	19	■							NA
610658	RS-6	H-200	Sngl	25	2500	0	6750	19			■	■				3T-6T
610206	RS-7X	H-200	Sngl	25	2500	0	7512	18	■							NA
610207	RS-7	H-200	Sngl	25	2500	0	7512	18		■	■	■				3T - 6T
610057	RS-12	H-250	Sngl	40	3000	0	13014	18			■	■	■	■		6T - 12T
610058	RT-9	H-250	Two	50	3000	4925	9850	31 / 63			■	■	■	■		4T - 8T
610059	RT-12	H-250	Two	50	3000	5753	12330	25 / 54			■	■	■	■		6T - 12T
610060	RT-20	H-300	Two	50	3000	11331	22662	13 / 25						■	■	12T - 20T
610061	RT-30	S-400	Two	50	3000	15234	30470	9 / 19							■	15T - 25T
610480	RT-40	130mm	Two	50	3000	19757	39514	7 / 15							■	15T - 25T
610589	RV-100	150mm	Var	150	5000	26234	98751	11 / 17							■	30T - 40T
610600	RV-150	177mm	Var	150	5000	41905	157741	7 / 10							■	35T - 45T
610577	RV-200	177mm	Var	150	5000	53379	200842	5 / 8							■	45T - 60T
610547	RV-300	200mm	Var	150	5000	80378	302428	7 / 6							■	60T-90T

CONNECTIONS: H-200 = 2" Hex, R-256 = 2 9/16" Round, H-250 = 2 1/2" Hex, H-300 = 3" Hex, and S-400 = 4" Square, MM Hubs are Square

Note: Revolution Drive units are not recommended for DTH and will not be covered under warranty for damage due to down the hole drilling.

VARIABLE SPEED MODELS MUST HAVE A DRAIN LINE.

www.pengoattachments.com

