



“Rotary Offset Silt Fence Plow Features”

Dedicated Skid Loader Quick – Attach Model

Model RT-SFP36 Rotary Skid loader Silt Fence Plow 36”

**Approved for Min. 60 hp skid loaders with a minimum weight of
6000#s and up**

Steel tracks over rubber tires or rubber tracked machines required

Standard Features

- Dedicated universal skid loader quick-attach hookup
- Install silt fence down the center or offset to the left or right hand sides
- Offsetting ability 18” and 31” either side of center – pivots plow to edge of track or tire
- Weight 875 lbs
- 36” fabric chute can install 36” and smaller fabric sizes
- Fabric chute has stainless steel parts in key wear areas
- 1” thick straight mole board knife
- Replaceable 2” wide hardened knife point
- Two position knife setting to match machine size
- Spring loaded hardened 16” diam. cutting coulter cuts through soil, trash and tree roots
- Grade 8 5/8” x 4 1/2” shear bolt protection with hardened bushing
- Forklift/hoist slots for easy moving
- Rear pivot has a 90 degree swing to either side of center for tight turning
- Massive 2” x 8” grease able pivot pins
- 6” x 4” x 3/8” structural steel main beam construction
- Swing dampening cylinder with transport lock
- Fabric Tension Spring with 16” diameter fabric retention plate
- Up to 1500’ rolls of silt fence material can be used
- Can install silt fence from 6” deep to 20” deep
- Retractable storage legs with pads for stability

Model RS-SFP42 Rotary Skid Loader Silt Fence Plow 42” Model

Same Features as above plus the following:

- 42” Fabric chute can install 42” and smaller fabric sizes
- Weight 920 lbs
- Fabric curtain is standard equipment

Model RS-SFP48 Rotary Skid Loader Silt Fence Plow 48” Model

Same Features as above plus the following:

- 48" Fabric chute can install 48" and smaller fabric sizes
- Weight 958 lbs
- Fabric curtain is standard equipment