

"Rotary Offset Silt Fence Plow Features"

Dedicated Three Point Hitch Attachment Model

Model RT-SFP36 Rotary Tractor Silt Fence Plow 36"

Please Note: Hyd. Top link cylinder required for proper operation of "The Silt Fence Plow" when attached to the 3 point hitch of a tractor

Approved for Min. 45 Hp FWD with minimum weight of 3500# - up to 125 Hp FWD Tractors



Standard Features

- Dedicated Cat. I and II three point hookup
- Install silt fence down the center or offset to the left or right hand sides
- Offsetting ability 18" and 31" either side of center- pivots plow to edge of tire or track
- Weight 750 lbs
- 36" fabric chute can install 36" and smaller fabric sizes
- Fabric chute has stainless steel parts in key wear areas
- 1" thick straight mole board knife
- Replaceable 2" wide hardened knife point
- Two position knife setting to match tractor size
- Spring loaded hardened 16" diam. cutting coulter to cut through soil, trash and tree roots
- Grade 8 5/8" x 4 1/2" shear bolt protection
- Forklift/hoist slots for easy moving
- Rear pivot has a 90 degree swing to either side of center for tight turning
- Massive 2" x 8" grease able pivot pins
- 6" x 4" x 3/8" structural steel main beam construction
- Swing dampening cylinder with transport lock
- Fabric Tension spring with 16" diameter fabric plate
- Up to 1500' rolls of silt fence material can be used
- Can install silt fence from 6" deep to 20" deep
- Retractable storage legs with pads for stability

Model RT-SFP42 Rotary Tractor Silt Fence Plow 42" Model

Same features as above plus the following:

- 42" fabric chute can install 42" and smaller fabric sizes
- Weight 795 lbs
- Fabric curtain is standard equipment

Model RT-SFP48 Rotary Tractor Silt Fence Plow 48" Model

Same features as above plus the following:

- 48" fabric Chute can install 48" and smaller fabric sizes
- Weight 833 lbs

- Fabric curtain is standard equipment