

Specifications for Rotary Silt Fence Plow  
 Rotary Tractor Silt Fence Plow  
 Model RT-SFP

Model	RT-SFP36	RT-SFP42	RT-SFP48
Height: Top Knife Setting Bottom Knife Setting	76" 71"	76" 71"	76" 71"
Width with legs down			
Width with legs up	46"	46"	46"
Length	112"	123"	129"
Weight	750 lbs.	795 lbs.	833 lbs.
Shipping weight	825 lbs	870 lbs	908 lbs
Cutting coulter	Spring loaded with 16" hardened fluted blade	Spring loaded with 16" hardened fluted blade	Spring loaded with hardened fluted blade
Rear pivot Turning	90° either side of center	90° either side of center	90° either side of center
Rear pivot	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings
Front rotary pivot pin	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings
Offsetting ability	18" and 31" either side of center	18" and 31" either side of center	18" and 31" either side of center
Main beam size	6" x 4" x 3/8"	6" x 4" x 3/8"	6" x 4" x 3/8"
Forklift slots	Standard equipment	Standard equipment	Standard equipment
Mole board knife	1" thick / two position	1" thick / two position	1" thick / two position
Replaceable knife point	2" wide hardened steel	2" wide hardened steel	2" wide hardened steel
Shear bolt protection	5/8" x 4 1/2" grade 8 bolt	5/8" x 4 1/2" grade 8 bolt	5/8" x 4 1/2" grade 8 bolt
Fabric retention plates	16" diameter	16" diameter	16" diameter
Fabric tension spring	Standard equipment	Standard equipment	Standard equipment

Swing dampening cylinder	Self contained/standard equipment	Self contained/standard equipment	Self contained/standard equipment
3-Point hitch attachment	Cat. I and II hookup pins	Cat. I and II hookup pins	Cat. I and II hookup pins
Fabric chute / stainless steel in key wear areas	Can install 36" and smaller fabric sizes	Can install 42" and smaller fabric sizes	Can install 48" and smaller fabric sizes
Fabric curtain	Optional	Standard	Standard
Digging depth	20" maximum	20" maximum	20" maximum