

## SWEEPERS FOR WHEEL LOADERS AND TRUCKS

## LA - Truck and Wheel Loader Angle Sweeper - Hydraulic Drive

- Heavy duty cleanup
- Dual motors powered from loader hydraulics
- 20-50 GPM flow required (2,000-3,500 psi)
- Casters and parallel arm mounting to follow ground contour are included
- 32" brush diameter
- 8', 9' brush widths available
- Various quick attach and pin-on mounts available
- Mechanical angle standard, hydraulic optional
- Quick change core



Specifications	<del>21196</del>	21197	<u>21108</u>	21109
Max Width at 0° Articulation	106.5"	106.5''	118.5''	118.5''
Max Length at 0° Articulation	74.5''	74.5''	74.5''	74.5''
Max Width at Full Articulation	103.0''	103.0''	113.0''	113.0''
Max Length at Full Articulation	89.0''	89.0''	92.5''	92.5''
Motors	single	dual	single	dual
Brush Diameter	32.0''	32.0"	32.0"	32.0"
Weight (lbs.)	1,675	1,700	1,925	1,950

Range of Hydraulic Oil Flow			
Single Motor	25 cubic inches	<del>12 to 25 gpm</del>	
Dual Motor	18 cubic inches	18 to 36 gpm	

Range of Hydraulic Oil Pressure			
Single Motor	25 cubic inches	<del>3000 psi</del>	
Dual Motor	18 cubic inches	3500 psi	