

BALE SPEARS

The current generation bale spear line provides many different spear lengths, more space for spear maintenance and replacement, and extensions for hauling and stacking bales efficiently.



V50 ROUND BALE SPEAR MACHINED // BSM
 2" X 48" MACHINED SPEAR,
 1 1/4" X 18" MACHINED STABILIZERS
BSM48 REPLACES DISCONTINUED BSV48



V50 ROUND BALE SPEAR // BS
 49" CONUS 2 SPEAR, 1 1/4" X 18" MACHINED STABILIZERS
BS49 REPLACES DISCONTINUED BSV48F



V60 ROUND BALE SPEAR // BSH
 49" CONUS 3 SPEAR, 1 1/2" X 21" MACHINED STABILIZERS



V50 DOUBLE ROUND BALE SPEAR // BDR
 49" CONUS 2 SPEARS
 OPTIONAL 24" & 48-60" EXTENSIONS AVAILABLE



V60 DOUBLE ROUND BALE SPEAR // BDRH
 49" CONUS 3 SPEARS
 OPTIONAL 24" & 48-60" EXTENSIONS AVAILABLE



V50 BALE FORK // BF
 49" CONUS 2 SPEARS
BF49 REPLACES DISCONTINUED BFV48F
 OPTIONAL 24" EXTENSION AVAILABLE



V60 BALE FORK // BFH
 49" CONUS 3 SPEARS
 OPTIONAL 24" EXTENSION AVAILABLE



MODEL	BSM / BS / BSH	BDR / BDRH	BF / BFH
Overall Width (in.)	45.1	95.8	49.3
Overall Height (in.)		22.4	
Overall Depth (in.)	54.3 / 53.2 / 59.8	51.4 / 56.1	51.4 / 56.1
Main Spear Useable Length (in.)	42.3' / 43.2 / 47.9	43.2 / 47.9	43.2 / 47.9
Stabilizer Spear Useable Length (in.)	16.0	-	-
Bottom Spear Space (in.)	31.5	29.0 31.0 29.0	42.6 42.4
Approximate Weight (lbs)	230 / 215 / 225	410 / 450	195 / 215
Capacity, With Bale Against Frame (lbs)	2500	5000	3300

¹Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).



V50 COMBO BALE SPEAR // BSC

49" CONUS 2 MAIN SPEAR
 CHOOSE 32" (BSC32) OR 39" (BSC39) CONUS 1 STABILIZERS
 UTILIZES SAME FRAME AS BSS MODELS
BSC32 REPLACES DISCONTINUED CBV48F
 OPTIONAL 24" EXTENSION AVAILABLE



V60 COMBO BALE SPEAR // BSCH

49" CONUS 2 MAIN SPEAR
 CHOOSE 32" (BSCH32), 39" (BSCH39) OR
 49" (BSCH49) CONUS 2 STABILIZERS
 OPTIONAL 24" & 48-60" EXTENSIONS AVAILABLE



V50 SQUARE BALE SPEAR // BSS

CHOOSE 32" (BSS32) OR 39" (BSS39) CONUS 1 SPEARS
 UTILIZES SAME FRAME AS BSC MODELS
BSS32 REPLACES DISCONTINUED SSV48F
 OPTIONAL 24" EXTENSION AVAILABLE



V50 BIG SQUARE BALE SPEAR // BAS

CHOOSE 32" (BAS32) OR 39" (BAS39) CONUS 1 SPEARS
BAS32 REPLACES DISCONTINUED BASS66F
 OPTIONAL 24" & 48-60" EXTENSIONS AVAILABLE



V60 BIG SQUARE BALE SPEAR // BASH

CHOOSE 32" (BASH32), 39" (BASH39) OR
 49" (BASH49) CONUS 2 SPEARS
 OPTIONAL 24" & 48-60" EXTENSIONS AVAILABLE



OPTION: 24" BALE SPEAR EXT. (EK24)
 Increases frame height by 24" to haul more bales per load. Compatible with current bale spear models only.



OPTION: 48-60" BALE SPEAR EXT. (EK60)
 Adjustable extension to set additional frame height to 48" or 60". Compatible with current bale spear models only.

48-60" BALE SPEAR EXTENSION UPGRADE KIT (EKU60)

Converts an existing 24" Bale Spear Extension (EK24) to a 48-60" extension (EK60). Requires 24" Bale Spear Extension. EK24 not included.

MODEL	BSC: 32 / 39	BSCH:32/39/49	BSS: 32 / 39	BAS: 32 / 39	BASH:32/39/49
Overall Width (in.)	49.3	71.8	49.3	71.8	71.8
Overall Height (in.)	22.4				
Overall Depth (in.)	51.4 / 58.4	51.4 / 58.4 / 68.4	34.8 / 41.8	34.8 / 41.8	34.8 / 41.8 / 51.8
Main Spear Useable Length (in.)	43.2	43.2	26.6 / 33.6	26.6 / 33.6	26.2 / 33.2 / 43.2
Stabilizer Spear Useable Length (in.)	26.6 / 33.6	26.2 / 33.2 / 43.2	-	-	-
Bottom Spear Space (in.)	21.5	22.0 / 21.0 / 22.0	21.5	22.0 / 21.0 / 22.0	22.0 / 21.0 / 22.0
Approximate Weight (lbs)	240 / 252	355 / 365 / 390	220 / 230	295 / 310	310 / 320 / 345
Capacity, With Bale Against Frame (lbs)	3300	5000	3300	5000	5000