

# MINI SKID STEER

## V20 MINI SKID STEER ANGLE BROOM

Available widths 48" & 60"

Direct drive Eaton® motor and exclusive self-centering swing linkage system for optimal sweeping.

### CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.



Standard with manual angle.  
Standard with 26" diameter poly/wire wafers; all poly wafers also available.

<b>10-18 GPM</b> RECOMMENDED FLOW RATE	<b>DIRECT</b> DRIVE MOTOR	<b>MANUAL &amp; HYDRAULIC</b> ANGLE AVAILABLE	<b>GREATER THAN 500 LB</b> LOADER OPERATING CAPACITY
--	------------------------------	--	---

1. SWING LINKAGE SYSTEM SELF-CENTERS BROOM WHEN ANGLED
2. RECESSED & GUARDED MOTOR
3. HD 1.25" GREASEABLE BEARING
4. REPLACE WAFERS EASILY WITHOUT DISCONNECTING HOSES. STANDARD WITH POLY/WIRE WAFERS.
5. STANDS FLIP DOWN TO PROTECT BRISTLES DURING STORAGE



**OPTION:  
HYDRAULIC  
ANGLE**  
Angle the broom from the loader.

MODEL	CAB48	CAB60
Sweeping Width, Straight (in.)	48.0	60.0
Sweeping Width, Full Angle (in.)	42.8	53.5
Loader Track Width Coverage, Full Angle (in.)	38.0	48.0
Overall Width (in.)	54.3	66.3
Overall Width, Full Angle (in.)	58.5	68.5
Overall Height/Depth, Straight (in.)	27.7 / 56.9	
Max Broom Angle (degrees)	28	
Number of 26 Inch Diameter Wafers	23	29
Recommended Flow Rate (GPM)	10-18 Standard Flow Only	
Approximate Weight (lbs)	495*	530*
Recommended Loader Capacity	Greater than 500 lbs	

\*ASV® mount adds approximately 30 lbs and Bobcat® mount adds 25 lbs to model weight.