

MINI SKID STEER

V20 MINI SKID STEER TILLER

Available width 48"

High torque Eaton® motor and heat-treated tines deliver ground breaking performance.

CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.



EATON

Char-Lynn

10-18 GPM
RECOMMENDED
FLOW RATE

DIRECT DRIVE MOTOR
WITH RELIEF VALVE PROTECTION

GREATER THAN
500 LB
LOADER OPERATING CAPACITY

1. BOLT-ON, HEAT-TREATED DUAL-EDGE TINES FOR BI-DIRECTIONAL OPERATION & LONGEVITY
2. ADJUSTABLE SKID SHOES PROVIDE 4"-6" TILLING DEPTH
3. TILLER SHAFT SUPPORTED BY 2" DIAMETER BEARINGS ON EACH SIDE
4. GUARDED MOTOR ON BOTTOM & SIDES



MODEL	CTRL48
Working Width (in.)	48.0
Overall Width (in.)	64.9
Overall Height (in.)	22.2
Overall Depth (in.)	26
Tilling Depth (in.)	6.0
Drum Diameter (in.)	18.5
Number of Tines	24
Recommended Flow Rate (GPM)	10-18
Approximate Weight (lbs)	470*
Recommended Loader Capacity	Greater than 500 lbs

*Bobcat® mount adds approximately 10 lbs to model weight.