

V20 MINI SKID STEER LAND LEVELER

Available widths 36", 42", 48" & 54"

Efficiently cut, grade and level soil. Perfect for site preparation.



CHOOSE FROM THREE MINI SKID MOUNTS:

- MINI UNIVERSAL (All brands except Bobcat® and ASV®)
- BOBCAT® Mini
- ASV® Mini*

NOTE: None of the above are compatible with universal skid steer mount.

*ASV mini skid mount not available for CLL36 & CLL42. ASV® mini skid mount only available for CLL48 and CLL54.

36"-54"

WIDTHS AVAILABLE

OPTIONAL SCARIFIER

W/ 4.6" DIGGING DEPTH

LESS THAN 1650 LB

LOADER OPERATING CAPACITY

1. DUAL ½" X 4" CUTTING EDGES FOR PRODUCTIVE OPERATION IN FORWARD & REVERSE
2. OPEN, LOW BACK DESIGN FOR BETTER CUTTING EDGE VISIBILITY
3. FLAT TOP FOR CARRYING OBJECTS



OPTION: SCARIFIER

AR400, 1/2" thick scarifying teeth cut 4.6" deep to break up compact soil while leveling in reverse.

Manually lock into a secure storage position when not in use.

MODEL	CLL36	CLL42	CLL48	CLL54
Overall Width (in.)	36.0	42.0	48.0	54.0
Overall Height (in.): Toro® / Bobcat® / ASV®	14.9 / 20.9 / 17.2			
Overall Depth (in.)	46.2			
Weld-On Edges (in.)	½ x 4			
Approximate Weight (lbs)	185 ¹	200 ¹	210 ¹	225 ¹
Recommended Loader Capacity	Less than 1650 lbs			

¹ASV® & Bobcat® mounts add approximately 10 lbs to model weight.