

MINI SKID STEER

V20 MINI SKID STEER SNOW BLOWER

Available width 48"

Two-stage design with paddle-style auger chews through any type of snow, and direct drive motor throws it up to 30 feet.



CHOOSE FROM THREE MINI SKID MOUNTS:

- MINI UNIVERSAL (All brands except Bobcat® and ASV®)
- BOBCAT® Mini
- ASV® Mini

NOTE: None of the above are compatible with universal skid steer mount.



10-18 GPM RECOMMENDED FLOW RATE	30.0' MAX THROWING DISTANCE	22.0" CUT HEIGHT	GREATER THAN 600 LB LOADER OPERATING CAPACITY
--	--	----------------------------	---

1. ANGLED AUGER PADDLES CHEW THROUGH SNOW & CONTINUALLY FEED THE FAN
2. DIRECT DRIVE PARKER® MOTORS WITH RELIEF VALVES
3. ADJUSTABLE & REVERSIBLE POLY SKID SHOES DESIGNED TO HOP OVER SMALL OBSTRUCTIONS
4. 3/16" FAN HOUSING REDUCES DISTORTION
5. 270° HYDRAULIC CHUTE ROTATION WITH DEFLECTOR CONTROL FROM PLATFORM OR IN CAB
6. GUARD PROTECTS VALVES & ELECTRICAL COMPONENTS
7. 1/2" x 6" REVERSIBLE STEEL BOLT-ON EDGE

MODEL	CSB48-18
Overall Width / Cut Width (in.)	48.5 / 48.0
Height: Max w. Chute / Cut (in.)	54.0 / 21.9
Overall Depth (in.)	37.2
Fan: Diameter / Depth (in.)	17.5 / 5.1
Auger Diameter (in.)	14.0
Throwing Distance	Up to 30 Feet
Recommended Flow Rate (GPM)	10-18
Approximate Weight (lbs)	610 ^{1,2}
Recommended Loader Capacity	Greater than 600 lbs

¹Bobcat® mount adds approximately 15 lbs to model weight, and ²ASV® mount adds 30 lbs.