

V20 MINI SKID STEER SKELETON GRAPPLE

Available widths 36", 42" & 48"
 Open-sided design for hauling brush and logs. Open bottom allows dirt to fall through.



0.25" GRADE 50 STEEL TINES	30.3" JAW OPENING	5.9" TINE SPACING	> 500 LB LOADER OPERATING CAP.
-----------------------------------	--------------------------	--------------------------	--

1. EVERY TINE IS MADE FROM ONE PIECE OF STEEL FOR MAXIMUM RIGIDITY
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE
3. STANDARD WITH CYLINDER GUARD

CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.

	MODEL CSGV36	CSGV42	CSGV48
Overall Width (Inches)	36.0	42.0	48.0
Height: Overall / Bucket (Inches)	26.6 / 24.1		
Overall Depth (Inches)	31.9		
Number of Tines (With Sides)	7	8	9
Space Between Tines (Inches)	5.9		
Tine Thickness (Inches)	0.25 ¹		
Cylinder Bore / Stroke (Inches)	2.0 / 6.0		
Cylinder Pins / Hinge Pins Dia (In)	1.0 / 1.0		
Grapple Jaw Opening (Inches)	30.3		
Approximate Weight (Pounds)	240 ²	265 ²	280 ²
Recommended Loader Capacity	Greater than 500 pounds		

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).

²ASV® mount adds approximately 30 pounds and Bobcat® mount adds 15 pounds to model weight.