

V40 OPEN FRONT ROTARY BRUSH CUTTER

Available Widths 60", 66", 72" & 78"

Virnig's most popular cutter designed to excel in the field and set the gold standard for direct drive open front brush cutters.




Char-Lynn

Do not operate rotary brush cutter without a shatterproof cab on loader.

<p>5.0" CUT CAPACITY</p>	<p>60"-78" FOUR CUT WIDTHS</p>	<p>14-32 GPM FOUR MOTOR OPTIONS STANDARD & HIGH FLOW</p>	<p>3500 PSI MAX OPERATING PRESSURE</p>	<p>UP TO 270 LB FLYWHEEL WEIGHT</p>
-------------------------------------	---	---	---	--

DETAIL UNDER DECK





- 1. DIRECT DRIVE EATON® MOTOR WITH PRESSURE RELIEF, MOTOR & SPINDLE GUARDS PREVENT DOWNTIME
- 2. HYDRAULIC BRAKING STOPS FLYWHEEL WITHIN 10 SECONDS & LIFT LIMIT CHAIN PROTECTS OPERATOR
- 3. ROUNDED FLYWHEEL TO GLANCE OFF OBJECTS & ENSURE UNIFORM ENERGY DISTRIBUTION TO EXTEND DRIVETRAIN LIFE
- 4. 3 DOUBLE-SIDED BLADES FEATURE UP TO 39" OF ACTIVE CUTTING EDGE, 3X MORE THAN 2-BLADE CUTTERS, WHILE MACHINE SHARPENED EDGES CUT LIKE AXES TO PROCESS MATERIAL & DELIVER A MANICURED FINISH
- 5. REPLACEABLE FRONT SKID SHOES DESIGNED TO CUT GROUND LEVEL & HELP GLIDE OVER ROUGH TERRAIN
- 6. ANGLED REAR DECK CORNERS IMPROVE MATERIAL FLOW & TAPERED REAR DECK RUNNERS REDUCE GROUND DISTURBANCE

MODEL	BBC60-O	BBC66-O	BBC72-O	BBC78-O
Cut Width (in.)	60.0	66.0	72.0	78.0
Overall Height / Width / Depth (in.)	21.5 / 66.0 / 69.8	21.5 / 72.0 / 75.8	21.5 / 78.0 / 81.8	21.5 / 84.0 / 87.8
Deck Height (in.)	7.5			
Minimum Cut Height (in.)	1.8			
Cutting Capacity, Diameter (in.)	5.0			
Deck Thickness, Top / Side (in.)	0.25			
Recommended Flow Rate (GPM)	14-25 Standard Flow / 26-32 High Flow			
Max Operating Pressure (PSI)	3500			
Flywheel Weight (lbs)	265	265	270	270
Approximate Weight (lbs)	1335 ¹	1410 ¹	1505 ¹	1590 ¹
Recommended Operating Cap (50%)	Less than 4200 pounds			

¹Standard flow weight. High flow models add approximately 40 lbs to model weight.