

V60 FOUR-CYLINDER PIPE PALLET FORK GRAPPLE

Four-cylinder design applies consistent pressure to secure long pipe over uneven terrain.



1. 48" OR 60" ITA CLASS II FORGED TINES

2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS



	MODEL	PPFG448	PPFG460
Overall Width (Inches)		69.0	
Overall Height: Open / Closed (In)		62.0 / 42.5	
Overall Depth (Inches)	58.0		70.0
Grapple Arm Width (Inches)		11.4	
Grapple Arm Depth (Inches)		30.4	
Tine Space: Min / Max (Inches)		8.9 / 49.0	
Tine: Length / Width / Thickness (In)	48.0 / 4.0 / 1.75		60.0 / 4.0 / 1.5
Cylinder Bore / Stroke (Inches)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia (In)		1.25 / 1.25	
Lift Capacity (Pounds)	6200		5500
Approximate Weight (Pounds)	1110		1065
Recommended Loader Capacity		Greater than 1500 pounds	

V60 TWO-CYLINDER PIPE PALLET FORK GRAPPLE

Two-cylinder independent clamp arms open to near vertical for handling palletized material.



1. 48" OR 60" ITA CLASS II FORGED TINES

2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

	MODEL	PPFG248	PPFG260
Overall Width (Inches)		70.8	
Overall Height: Open / Closed (In)		81.4 / 40.4	
Overall Depth (Inches)	56.0		67.5
Grapple Arm Width (Inches)		8.3	
Tine Space: Min / Max (Inches)		8.9 / 49.1	
Tine: Length / Width / Thickness (In)	48.0 / 4.0 / 1.75		60.0 / 4.0 / 1.5
Cylinder Bore / Stroke (Inches)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia (In)		1.25 / 1.25	
Lift Capacity (Pounds)	6200		5500
Approximate Weight (Pounds)	920		925
Recommended Loader Capacity		Greater than 1500 pounds	