

V70 CWL GENERAL PURPOSE BUCKET

Available widths 72", 78", 84", 90" & 96"

UNIVERSAL SKID STEER MOUNT ONLY
 · ISO or Pin-On Mounts Not Available

High-strength bucket built for digging, grading, leveling and handling material in rugged conditions.



Not compatible with skid steers and track loaders.
 Exclusively designed for CWLs with universal quick attach mount.

AVAILABLE EDGE OPTIONS
 See page 90 for additional information.



38.8" DEPTH	28.3" HEIGHT	1.0-1.4 YD HEAPED CAPACITY (VARIES BY MODEL)	GREATER THAN 1800 LB LOADER OPERATING CAPACITY AT FULL TURN
-----------------------	------------------------	---	--

1. FLAT TOP HELPS OPERATORS GAUGE WHEN BUCKET IS LEVEL
2. CURVED INSIDE FOR EASIER MATERIAL CLEANOUT & GRADING BEND FOR OPTIMAL REVERSE GRADING
3. 1/4" THICK SHELL & SIDE PLATES
4. 1" x 6" WELD-ON EDGE
5. 1/2" x 4" WEAR BARS PROTECT THE BUCKET BOTTOM



OPTION: SIDE CUTTERS
 Exclusive reversible design. Improves performance in hard, compacted soils and extends the life of the bucket sides. Not compatible with Toothbars.

MODEL	WGP72	WGP78	WGP84	WGP90	WGP96
Width: Overall / Inside (in.)	73.5 / 71.3	79.5 / 77.3	85.5 / 83.3	91.5 / 89.3	97.5 / 95.3
Overall Height (in.)	28.3				
Depth: Overall / Inside (in.)	38.8 / 34.3				
Struck Capacity (cu. ft. / cu. yd.)	23.6 / 0.87	25.5 / 0.95	27.5 / 1.02	29.5 / 1.09	31.5 / 1.17
Heaped Capacity (cu. ft. / cu. yd.)	28.3 / 1.04	30.6 / 1.14	33.0 / 1.22	35.4 / 1.31	37.8 / 1.40
Bucket Back Angle (degrees)	65				
Shell Thickness (in.)	0.25				
Side Plate Thickness (in.)	0.25				
Structural Wear Bars Under Bucket (1/2" x 4")	5				
Approximate Weight (lbs)	835	880	925	975	1020
Recommended Loader Capacity at Full Turn	Greater than 1800 lbs				