

# V70 CWL HIGH CAPACITY GEN. PURPOSE BUCKET

Available widths 72", 78", 84", 90", 96" & 101"

**UNIVERSAL SKID STEER MOUNT ONLY**  
 · ISO or Pin-On Mounts Not Available

Designed taller and deeper than V70 General Purpose Bucket for 15% more capacity.



Not compatible with skid steers and track loaders.  
 Exclusively designed for CWLs with universal quick attach mount.

**AVAILABLE EDGE OPTIONS**  
 See page 90 for additional information.




**STANDARD BOLT-ON**



**WELD-ON TEETH**

<b>40.8"</b> DEPTH	<b>32.1"</b> HEIGHT	<b>1.2-1.6 YD</b> HEAPED CAPACITY (VARIES BY MODEL)	<b>GREATER THAN 1800 LB</b> LOADER OPERATING CAPACITY AT FULL TURN
-----------------------	------------------------	---	--

1. FLAT TOP HELPS OPERATORS GAUGE WHEN BUCKET IS LEVEL
2. CURVED INSIDE FOR EASIER MATERIAL CLEANOUT & GRADING BEND FOR OPTIMAL REVERSE GRADING
3. 1/4" THICK SHELL & SIDE PLATES
4. 1" x 6" WELD-ON EDGE
5. 1/2" x 4" WEAR BARS PROTECT THE BUCKET BOTTOM



**OPTION: SIDE CUTTERS**

Exclusive reversible design. Improves performance in hard, compacted soils and extends the life of the bucket sides. Not compatible with Toothbars.

MODEL	WHC72	WHC78	WHC84	WHC90	WHC96	WHC101
Width: Overall / Inside (in.)	73.5 / 71.3	79.5 / 77.3	85.5 / 83.3	91.5 / 89.3	97.5 / 95.3	101.5 / 99.3
Overall Height (in.)	32.1					
Depth: Overall / Inside (in.)	40.8 / 36.5					
Struck Capacity (cu. ft. / cu. yd.)	27.0 / 1.0	29.30 / 1.08	31.60 / 1.17	33.80 / 1.25	36.10 / 1.34	37.60 / 1.40
Heaped Capacity (cu. ft. / cu. yd.)	32.4 / 1.20	35.20 / 1.30	37.90 / 1.40	40.60 / 1.50	43.30 / 1.60	45.10 / 1.68
Bucket Back Angle (degrees)	65					
Shell Thickness (in.)	0.25					
Side Plate Thickness (in.)	0.25					
Structural Wear Bars Under Bucket (1/2" x 4")	5					
Approximate Weight (lbs)	940	990	1040	1100	1150	1185
Recommended Loader Capacity at Full Turn	Greater than 1800 lbs					