## V70 CWL SNOW/LIGHT MATERIAL BUCKET

Available widths 72", 78", 84", 96" & 101"

Provides the highest capacity for handling snow, grain, mulch, and other loose or low-density materials.

UNIVERSAL SKID STEER MOUNT ONLY · ISO or Pin-On Mounts Not Available



Not compatible with skid steers and track loaders. Exclusively designed for CWLs with universal quick attach mount.

47.3" DEPTH

36.3" HEIGHT

1.7-2.3 YD HEAPED CAPACITY (VARIES BY MODEL)

AVAILABLE EDGE OPTIONS See page 90 for additional information.





GREATER THAN 2400 LB LOADER OPERATING CAPACITY AT FULL TURN

- 1. PROVIDES FULL ROLLBACK WITHOUT INTERFERING WITH Z-BAR LINKAGES
- 2. FLAT TOP HELPS OPERATORS GAUGE WHEN BUCKET IS LEVEL
- 3. CURVED INSIDE FOR EASIER MATERIAL CLEANOUT
- 4.1/4" THICK SHELL & SIDE PLATES
- 5.1" x 6" WELD-ON EDGE
- 6. 1/2" x 4" WEAR BARS PROTECT THE **BUCKET BOTTOM**





## **OPTION: SIDE CUTTERS**

Exclusive reversible design. Improves performance in hard, compacted soils and extends the life of the bucket sides. Not compatible with Toothbars.

MODEL	WLM72	WLM78	WLM84	WLM96	WLM101
Width: Overall / Inside (in.)	73.5 / 71.3	79.5 / 77.3	85.5 / 83.3	97.5 / 95.3	101.5 / 99.3
Overall Height (in.)			36.3		
Depth: Overall / Inside (in.)			47.3 / 43.0		
Struck Capacity (cu. ft. / cu. yd.)	38.20 / 1.42	41.40 / 1.53	44.60 / 1.65	51.10 / 1.89	53.20 / 1.97
Heaped Capacity (cu. ft. / cu. yd.)	45.80 / 1.70	49.70 / 1.84	53.50 / 1.98	61.30 / 2.27	63.80 / 2.36
Bucket Back Angle (degrees)	65				
Shell Thickness (in.)	0.25				
Side Plate Thickness (in.)	0.25				
Structural Wear Bars Under Bucket (1/2" x 4")			5		
Approximate Weight (lbs)	1020	1070	1120	1235	1270
Recommended Loader Capacity at Full Turn	Greater than 2400 lbs				