

DIGGING TREE PULLER

Dig, pull, and remove trees, stumps, and rocks.



32"
JAW OPENING

14"
BASE OPENING

GREATER THAN
1800 LB
LOADER OPERATING CAPACITY

- UNIQUE REPLACEABLE CUTTING EDGES FOR PUNCHING THROUGH HARD SOIL, CUTTING ROOTS & GRUBBING TREES
- FIXED JAW PROVIDES MAX STRENGTH & HELPS CENTER OBJECTS WHILE APPROACHING
- 1" THICK AR400 SERRATED JAWS & REPLACEABLE SERIES 23 TEETH FOR AGGRESSIVE DIGGING
- TREE STABILIZING SERRATIONS ON GUARD TOP & JAW BASE
- 3/8" THICK GUARD ANGLED FORWARD & ON CORNERS TO SHED FALLING TREES AWAY FROM LOADER
- 3.5" DIAMETER CYLINDER PROTECTED INSIDE FRAME & FROM STRESS WITH HARD STOP
- OPEN BACK DESIGN FOR QUICK CYLINDER ACCESS & DIRT CLEANOUT
- 3" TALL REAR BACK PLATE FOR EFFECTIVE SOIL BACK-DRAGGING
- OPTIMIZED HOSE ROUTING SAFEGUARDS HOSES FROM POTENTIAL DAMAGE

MODEL	DTP
Overall Width (in.)	50.4
Overall Height (in.)	48.4
Overall Depth (in.)	58.0
Guard Height / Width (in.)	27.4 / 46.4
Max Jaw Opening: Front / Base (in.)	32.0 / 14.0
Space Between Digging Teeth (in.)	6.2
Jaw Thickness (in.)	1.0*
Max Digging Depth (in.)	42.5
Cylinder Bore / Stroke (in.)	3.5 / 8.0
Cylinder Pins / Pivot Pins (in.)	1.6 / 2.2
Approximate Weight (lbs)	830
Recommended Loader Capacity	Greater than 1800 lbs

*Laminated 1/2" AR400 Plate (150,000 PSI Min Yield Strength) & 1/2" Grade 50 Plate (50,000 PSI Min Yield Strength).