

X20 MINI EXCAVATOR ROTARY BRUSH CUTTER

Available width 39"

Cut up to 3" diameter trees and clear brush faster with a 40" cut and up to 35% faster blade speed than 36" mini-ex cutters, all while keeping weight as low as 510 pounds.




Char-Lynn

Do not operate cutter without a shatterproof cab on excavator.

3.0" CUT CAPACITY	40" CUT WIDTH	13-25 GPM DIRECT DRIVE MOTOR	510-590 LB OVERALL WEIGHT	6500-15000 LB REC MINI-EX WEIGHT
-----------------------------	-------------------------	----------------------------------------	-------------------------------------	--------------------------------------------

DETAIL UNDER DECK
W/ OPTIONAL SIDE CURTAIN



**OPTION:
SIDE CURTAIN(S)**
Choose one or two bolt-on side curtains to reduce debris thrown.



**OPTION:
CARBIDE TEETH**
Shred material for a better finish.



**OPTION: BOLT-ON
HANGER BRACKET**
· Many options available!
· Note: Hanger bracket is not included.



- 1. NO CASE DRAIN REQUIRED. DIRECT DRIVE EATON® MOTOR WITH RELIEF VALVE PROTECTION
- 2. WEIGHT OPTIMIZED TO BE COMPATIBLE WITH 6500LB (3 TON) MINI EXCAVATORS
- 3. DECK DESIGNED TO LIMIT FLYING DEBRIS FOR SAFER OPERATION. ADD OPTIONAL SIDES FOR MAX DEBRIS CONTAINMENT
- 4. ROUNDED FLYWHEEL WITH 3 DOUBLE-SIDED BLADES BOUNCES OFF STUMPS. ADD OPTIONAL TEETH FOR A BETTER FINISH
- 5. STANDARD 90° HOSES, COUPLERS, MOTOR GUARD & SPINDLE GUARD
- 6. BOLT-ON MOUNTING INTERFACE TO QUICKLY CHANGE HANGER BRACKETS. VARIOUS HANGER BRACKETS AVAILABLE TO FIT MOST EXCAVATOR BRANDS

MODEL	XB39
Cut Width (in.)	40.1
Overall Width Without Sides / With Sides (in.)	52.5 / 53.1
Height: Overall / Deck (in.)	19.7 / 6.1
Overall Depth (in.)	45.1
Minimum Cut Height (in.)	2.3
Cutting Capacity, Diameter (in.)	3.0
Deck Thickness: Top / Side (in.)	3/16
Recommended Flow Rate (GPM)	13-25
Max Operating Pressure (PSI)	3500
Approximate Weight: No Sides / Both Sides (lbs)	510 ¹ / 590 ¹
[Optional] Carbide Teeth: Weight (lbs) / Qty	6 / 9
Approximate Operating Weight	Cutter (510) + Hanger + Options ²
Mini-Ex's Lowest Lift Capacity Over Side at Max Reach	Must Exceed Cutter Operating Weight ³
Recommended Mini Excavator Weight (lbs)	6500-15000

¹Weight doesn't include hanger bracket or tooth option.

²Add weight of cutter, hanger and options to determine operating weight. Hangers typically weigh between 80 and 150 pounds.

³Excavator's lowest lift capacity of any blade and boom orientation must exceed cutter operating weight.

Excavator lift capacities vary based on arm length, counterweight and open vs closed cab. Ensure the excavator configuration in the manufacturer's specs matches your machine's exact setup.